## ELEVATION CERTIFICATE

FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

O.M.B. No. 3067-0077 Expires July 31, 1999

## ATTENTION: Use of this certificate does not provide a waiver of the flood insurance purchase requirement. This form is used only to provide elevation information necessary to ensure compliance with applicable community floodplain management ordinances, to determine the proper insurance premium rate, and/or to support a request for a Letter of Map Amendment or Revision (LOMA or LOMR). You are not required to respond to this collection of information unless a valid OMB control number is displayed in the upper right corner of this form. Instructions for completing this form can be found on the following pages.

SECTION A PROPERTY INFORMATION					FOR INSURANCE COMPANY USE	
					POLICY NUMBER	
HANOVER STREET ADDRESS (Including Ac	SQUARE	CON DO		102	001001001000000	
STREET ADDRESS (Including Apt., Unit, Suite and/or Bldg. Number) OR P.O. ROUTE AND BOX NUMBER					COMPANY NAIC NUMBER	
OTHER DESCRIPTION (Lot and I	Block Numbers, etc.)		~			
BUILDING	Three,	JANOVE	ER SQUARE			
ST. SIMON	S ISIA	40		GEDRG	In 31522	
	SECTION B F	OOD INSURA	NCE RATE MAP (FIRM)			
Provide the following from t	he proper FIRM (See	Instructions):				
1. COMMUNITY NUMBER	2. PANEL NUMBER	3. SUFFIX	4. DATE OF FIRM INDEX	5. FIRM ZONE	6. BASE FLOOD ELEVATION	
130092	DAUA	Ο	7-17-95	AE	(in AO Zones, use depth)	
. Indicate the elevation dat	um system used on t	he FIRM for Ba	ase Flood Elevations (BFE	:): LANGVD '29	Other (describe on back	
<ol><li>For Zones A or V, where</li></ol>	no BFE is provided of	n the FIRM, ar	nd the community has esta	blished a BFE f	or this building site, indicate	
the community's BFE:	feet N	IGVD (or other	FIRM datum-see Section	B, Item 7).		
	SECTI	ON C BUILDI	NG ELEVATION INFORM	IATION		
(b). FIRM Zones V1-V30,	is at an elevation of BFE). The floor use	. The bottom o	of the lowest horizontal str feet NGVD (or other FIR nce level from the selected	M datum–see S	of the reference level from ection B, Item 7). 	
one) the highest grade	e adjacent to the build	ling. If no flood	n the selected diagram is I depth number is availabl ain management ordinand	e, is the building		
3. Indicate the elevation da under Comments on Pag the FIRM [see Section] equation under Commen	tum system used in o ge 2). (NOTE: If the B, Item 7], then conve tts on Page 2.)	etermining the elevation datur ert the elevation	above reference level ele n used in measuring the e ns to the datum system us	vations: WG levations is diffe sed on the FIRM	VD '29 Other (describe	
4. Elevation reference mark						
5. The reference level elevel (NOTE: Use of construct case this certificate will of will be required once con	tion drawings is only nly be valid for the bu	valid if the build ilding during th	uction 🗌 construction du ding does not yet have the e course of construction.	e reference level	floor in place, in which tion Elevation Certificate	
5. The elevation of the lowe Section B, Item 7).	est grade immediately	adjacent to the	e building is: 115	. 24 feet NGVD	(or other FIRM datum-see	
	S	ECTION D CO		DN .		
1. If the community official is not the "lowest floor" a floor" as defined by the o	is defined in the comi prdinance is:	nunity's floodpl ⊥L feet N	vations specifies that the ain management ordinand NGVD (or other FIRM datu	ce, the elevation		

## SECTION E CERTIFICATION

This certification is to be signed by a land surveyor, engineer, or architect who is authorized by state or local law to certify elevation information when the elevation information for Zones A1–A30, AE, AH, A (with BFE),V1–V30,VE, and V (with BFE) is required. Community officials who are authorized by local law or ordinance to provide floodplain management information, may also sign the certification. In the case of Zones AO and A (without a FEMA or community issued BFE), a building official, a property owner, or an owner's representative may also sign the certification.

Reference level diagrams 6, 7 and 8 - Distinguishing Features–If the certifier is unable to certify to breakaway/non-breakaway wall, enclosure size, location of servicing equipment, area use, wall openings, or unfinished area Feature(s), then list the Feature(s) not included in the certification under Comments below. The diagram number, Section C, Item 1, must still be entered.

I certify that the information in Sections B and C on this certificate represents my best efforts to interpret the data available. I understand that any false statement may be punishable by fine or imprisonment under 18 U.S. Code, Section 1001.

CERTIFIER'S NAME LICENSE NUMBER (or Affix Seal) GARY NEVILL GA R.L.S. NO. 2401 TITLE COMPANY NAME JURNEYOR LAND NAOL ADDRESS CITY 5 KOAD BRUNSWIC ARTERET GEORGIA 31525 SIGNATURE 912. 9 2 Copies should be made of this Certificate for: 1) community official, 2) insurance agent/company, and 3) building owner. A.C. = 15.7' COMMENTS: ON WITH ON PILES, SLAB BASEMENT PIERS, OR COLUMNS A A V ZONES ZONES ZONES ZONES ZONES REFERENCE REFERENCE LEVEL REFERENCE BASE FLOOD ELEVATION LEVE LEVEL BASE ADJACENT REFERENCE FLOOD LEVEL ELEVATION REFERENCE ADJACENT LEVEL GRADE ADJACENT GRADE

The diagrams above illustrate the points at which the elevations should be measured in A Zones and V Zones.

Elevations for all A Zones should be measured at the top of the reference level floor.

Elevations for all V Zones should be measured at the bottom of the lowest horizontal structural member.